

Package: regreplaceR (via r-universe)

November 16, 2024

Title Match and Replace Strings Based on Named Groups in Regular Expressions

Language en-US

Version 0.1.0

Date 2024-09-05

Author Gwang-Jin Kim [aut, cre]
(<https://orcid.org/0000-0002-2753-0883>)

Description An R6 class ``Replacer" provided by the package simplifies working with regex patterns containing named groups. It allows easy retrieval of matched portions and targeted replacements by group name, improving both code clarity and maintainability.

URL <https://github.com/gwangjinkim/regreplaceR>

Suggests rmarkdown, knitr

VignetteBuilder knitr

License MIT + file LICENSE

Encoding UTF-8

Imports R6

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Repository <https://gwangjinkim.r-universe.dev>

RemoteUrl <https://github.com/gwangjinkim/regreplacer>

RemoteRef HEAD

RemoteSha 65ab1d481fcfc9986cc08a6645cadd60682cf59f

Contents

groups	2
match_group	2
Replacer	3
replace_group	5

Index	7
--------------	----------

 groups

Extract Named Groups from a String Using a Regex Pattern

Description

This function extracts named groups from a given string using the specified regex pattern. Named groups in the pattern are denoted using `(?P<group_name>...)` syntax.

Usage

```
groups(pattern, s, ignore.case = FALSE)
```

Arguments

pattern	A character string containing the regex pattern with named groups.
s	A character string where the pattern will be searched.
ignore.case	Logical. If TRUE, the pattern matching is case-insensitive. Default is FALSE.

Value

A named list where names are the named groups and values are the extracted strings. If no matches are found, an empty list is returned.

Examples

```
pattern <- "(?P<name>\\w+) is (?P<age>\\d+)"
s <- "Jane is 25"
groups(pattern, s)
# $name
# [1] "Jane"
# $age
# [1] "25"
```

 match_group

Extract a Specific Named Group from a String

Description

This function extracts the value of a specific named group from a string using the provided regex pattern.

Usage

```
match_group(pattern, s, group_name, ignore.case = FALSE)
```

Arguments

pattern	A character string containing the regex pattern with named groups.
s	A character string where the pattern will be searched.
group_name	The name of the group to extract from the match.
ignore.case	Logical. If TRUE, the pattern matching is case-insensitive. Default is FALSE.

Value

The extracted value of the specified named group, or NULL if the group is not found.

Examples

```
pattern <- "(?P<name>\\w+) is (?P<age>\\d+)"
s <- "Jane is 25"
match_group(pattern, s, "name")
# [1] "Jane"
```

Replacer

Replacer Class for Regex Operations

Description

The Replacer class encapsulates regex operations using named groups. It allows matching and replacing based on named groups in a regex pattern.

Details

This class provides methods to match and replace parts of a string based on named groups in regular expressions.

Public fields

re A compiled regular expression pattern.

Methods**Public methods:**

- [Replacer\\$new\(\)](#)
- [Replacer\\$match\(\)](#)
- [Replacer\\$replace\(\)](#)
- [Replacer\\$clone\(\)](#)

Method `new()`: Create a new Replacer object with a regex pattern.

Usage:

```
Replacer$new(
  pattern = ".*?_(?P<date>\\d{8}-\\d{6}( \\(1\\))*)(?P<ext>\\.\\.+)$)"
)
```

Arguments:

pattern A character string with a regex pattern that includes named groups.

Returns: A new Replacer object.

Examples:

```
r <- Replacer$new(pattern=".*?_(?P<date>\\d{8}-\\d{6}( \\(1\\))*)(?P<ext>\\.\\.+)$")
```

Method match(): Match a string and extract a group by its name.

This method matches the string using the regex pattern and extracts the value of the group specified by group_name.

Usage:

```
Replacer$match(s, group_name)
```

Arguments:

s A character string to match against the regex pattern.

group_name The name of the group to extract from the match.

Returns: The matched value of the group or NULL if not found.

Examples:

```
r <- Replacer$new(pattern=".*?_(?P<date>\\d{8}-\\d{6})(?P<ext>\\.\\.+)$")
r$match("file_20230905-123456.txt", "date")
```

Method replace(): Replace the value of a matched group with a replacement string.

This method replaces the value of the matched group specified by group_name with the replacement string in the input string s.

Usage:

```
Replacer$replace(s, group_name, replacement)
```

Arguments:

s A character string to perform the replacement on.

group_name The name of the group to be replaced.

replacement The replacement string.

Returns: A modified string with the group replaced by the replacement.

Examples:

```
r <- Replacer$new(pattern=".*?_(?P<date>\\d{8}-\\d{6})(?P<ext>\\.\\.+)$")
r$replace("file_20230905-123456.txt", "date", "20240905-123456")
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
Replacer$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```

# Create a new Replacer object
r <- Replacer$new(pattern = ".*?(?P<date>\\d{8}-\\d{6})(?P<ext>\\.\\.+$)")

# Match a group within a string
r$match("file_20230905-123456.txt", "date")

# Replace the value of a matched group
r$replace("file_20230905-123456.txt", "date", "20240905-123456")

## -----
## Method `Replacer$new`
## -----

r <- Replacer$new(pattern=".*?(?P<date>\\d{8}-\\d{6}( \\(1\\))*)(?P<ext>\\.\\.+$)")

## -----
## Method `Replacer$match`
## -----

r <- Replacer$new(pattern=".*?(?P<date>\\d{8}-\\d{6})(?P<ext>\\.\\.+$)")
r$match("file_20230905-123456.txt", "date")

## -----
## Method `Replacer$replace`
## -----

r <- Replacer$new(pattern=".*?(?P<date>\\d{8}-\\d{6})(?P<ext>\\.\\.+$)")
r$replace("file_20230905-123456.txt", "date", "20240905-123456")

```

replace_group

Replace a Specific Named Group in a String

Description

This function replaces the value of a specific named group in a string using the provided regex pattern.

Usage

```
replace_group(pattern, s, group_name, replacer, ignore.case = FALSE)
```

Arguments

pattern	A character string containing the regex pattern with named groups.
s	A character string where the pattern will be searched.
group_name	The name of the group to be replaced.
replacer	A string that will replace the matched value of the specified group.
ignore.case	Logical. If TRUE, the pattern matching is case-insensitive. Default is FALSE.

Value

A modified string where the matched value of the specified group has been replaced by the replacer.

Examples

```
pattern <- "(?P<name>\\w+) is (?P<age>\\d+)"
s <- "Jane is 25"
replace_group(pattern, s, "name", "John")
# [1] "John is 25"
```

Index

`groups`, [2](#)

`match_group`, [2](#)

`replace_group`, [5](#)

`Replacer`, [3](#)